

# WON-330 | AUTOMATIC SLITTER REWINDER



The WON-330 narrow-web slitter rewriter is fully servo-driven and features taper tension control, top brand web guiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.



WON-330	S330	S420	S520
Max Speed	300 m/min	300 m/min	300 m/min
Max Web Width	300 mm	420 mm	520 mm
Min Slit Width	16 mm	16 mm	16 mm
Blades Installed	6 Sets	6 Sets	6 Sets
Max Unwind Dia	cp 700 mm	cp 700 mm	cp 700 mm
Max Rewind Dia	cp 400 mm	cp 400 mm	cp 400 mm
Power Supply	3 PH+N+PE	3 PH+N+PE	3 PH+N+PE
Air Supply	0.4 ~ 0.6 M Pa	0.4 ~ 0.6 M Pa	0.4 ~ 0.6 M Pa
Weight	1200 KGS	1200 KGS	1200 KGS
Overall	1800 x 1200 x 1400 mm	1800 x 1300 x 1400 mm	1800 x 1400 x 1400 mm
Main Power	7 kW	7 kW	7 kW



#### UNWINDER & WEB GUIDING

Unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. Max diameter 700 mm - 1000 mm roll capacity.

#### REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 700mm maximum rewind diameter.



#### COUNTER

High-quality German-made counting sensor - extra accessories needed for transparent film material.



#### SHEAR/RAZOR SLITTING AVAILABLE

Moveable shear slitting with standard high-pressure waste suction system and optional razor blades. Quick installation.



Fully  
servo-driven  
narrow-web  
slitter  
rewinder